

ChannelLine U

Product advantages

- ▶ Cover can be attached from above or inserted from the side
- ▶ For flush mounting
- ▶ High-quality deep recessed/surface-mounted profile

Features

- ▶ Homogeneous light line with Versa Inside from 120 LED/m
- ▶ Beam angle of approx. 50°

ChannelLine U

2500 mm (set of 10)

3000 mm (set of 10)

End cap (set of 2) lacquered

2500 mm

3000 mm

Application

- Shelves
- ▶ kitchen niches and top floors
- ▶ Interior cabinet lighting in the floor

Order information

▶ Use of feeders and connectors in the profile possible

Aluminium /

Opal

55 964 51

55 964 61

55 964 02

55 964 12

26 151 01

Black / Opal

55 964 55

55 964 65

55 964 06

55 964 16

26 151 05



Recommended for:

Technical details

Versa Inside 600 Versa Inside 1200 Versa Inside MaxiColor



Double-sided adhesive tape, 16x0.5 mm Double-sided adhesive tape, 9x0.5 mm 36 261 01 Assembly drawing

2500/3000 13 13 12 10.2 10.2 10.2

ChannelLine U2

Product advantages

- ▶ Cover can be attached from above or inserted from the side
- ▶ With filigree profile trim
- ▶ High-quality deep recessed/surface-mounted profile

Features

- ▶ Homogeneous light line with Versa Inside from 120 LED/m
- ▶ Beam angle of approx. 50°

ChannelLine U2

2500 mm (set of 10)

3000 mm (set of 10)

End cap (set of 2) lacquered

2500 mm

3000 mm

Application

- ▶ Shelves
- kitchen niches and top floors
- Interior cabinet lighting in the floor

Order information

▶ Use of feeders and connectors in the profile possible

Aluminium /

Opal

55 965 51

55 965 61

55 965 02

55 965 12

26 155 01

Black / Opal

55 965 55

55 965 65

55 965 06

55 965 16

26 155 05

Recommended for:

Technical details

Versa Inside 600 Versa Inside 1200 Versa Inside MaxiColor



