

ChannelLine i3

Product advantages

- ▶ High quality deep recessed profile
- ▶ Almost rimless illuminated surface
- ▶ Glare-free and concentrated light emission
- ▶ For flush mounting

Features

- ▶ Homogeneous light line with Versa Inside from 120 LED/m
- ▶ Narrow beam angle of approx. 35°

Application

- ▶ Accent lighting in display cabinets or shelves
- ▶ Flush with storage surfaces on the wall

Recommended for:

Versa Inside 1200

ChannelLine i3

	Aluminium / Opal
2500 mm	55 608 51
2500 mm (set of 10)	55 608 61
3000 mm	55 608 02
3000 mm (set of 10)	55 608 12
End cap (set of 2) lacquered	25 985 01

Accessories

	1 piece	10 piece
Double-sided adhesive tape, 9x0.5 mm	36 261 01	-
Cover profile dark 2000 mm	25 850 02	25 850 60
Cover profile dark 3000 mm	25 850 03	25 850 62

Versa Inside 600

Technical details



Assembly drawing 2500 / 3000 11

ChannelLine F

Product advantages

▶ Versatile

▶ Entry-level price

Features

▶ Beam angle and homogeneity can be varied with the milling depth

Application

▶ For milling into the wood

Order information

▶ Use of feeders and connectors in the profile possible

ChannelLine F

	Opal
2500 mm	55 664 51
3000 mm	55 664 02
3000 mm (set of 10)	55 641 13

Recommended for:

Technical details

Versa Inside 600 Versa Inside 1200



